

IC-F310 IC-F410



The photo shows actual size.

● Tough rugged construction

The highly dependable diecast aluminum chassis and polycarbonate front panel are resistant to impact.

● Flexible signalling capabilities

CTCSS and DTCS encoder/decoder and DTMF, 2-tone and 5-tone encoder are standard. Of course, 2-tone and 5-tone decoder functions are optionally available to suite a wide variety of signalling requirements. In addition, the IC-F310/F410 are compatible with the SmarTrunk II™ system*.

*Optional UT-105 SmarTrunk II™ Logic Board is required.

● Programmable key assign function

A limited number of switches (4) provide simple operation. Moreover, functions can be assigned to switches providing customization to suit specific needs.

● Selectable channel spacing

Versions are available that allow wide/narrow switching independently for each channel.

● Alphanumeric display

● Advanced programming package for IBM® PC

IBM® is a registered trademark of International Business Machines.



Icom Inc.

ADDITIONAL FEATURES

- Key backlight helps night operation
- 32 channels for 5-tone encoder
- Emergency call with single and repeat function
- 8 identities + group code for 5-tone decode (optional)
- Selectable digits for 5-tone decode indication
- Automatic ID transmission linked to PTT
- 51 frequencies for CTCSS (plus 1 programmable)
- Polarity selectable for DTCS
- 7 autodialing memories for DTMF
- Up to 5 characters for memory name indication
- Bank separation capability
- 5 scan channel groups
- 2 priority channels
- Automatic scan start and/or receive mute when mic. is on hook
- Automatic priority channel selection and/or mute release when mic. is off hook
- Normal and priority scan
- Scan start at power on
- Adjustable transmission release period to prevent noise burst at end of transmission when using CTCSS
- Remote monitoring capability (optional UT-96 required)
- Optional PIN code input to prevent operation by unauthorised persons
- Programmable minimum level for audio output
- Talk around function (temporary simplex operation on a duplex channel)
- Time-out timer
- Time-out ID transmission
- Penalty timer
- Transmit lockout (channel busy / repeater / reverse repeater)
- 2 selectable 'stun' functions (optional UT-96 required)
- Compact body provides easy installation

SPECIFICATIONS

GENERAL

- Frequency coverage*:

IC-F310	136-155 MHz 146-174 MHz
IC-F410	400-430 MHz 440-470 MHz 470-490 MHz 490-520 MHz

 *Varies according to versions.
- Number of channels : 32 (16 ch × 2 banks)
- Type of emission : BK50F3E (12.5 kHz; narrow)
16K0F3E (25 kHz; wide)
- Frequency stability : ±1500 Hz
- Operating temp. range: -30°C to +60°C
- Power supply voltage: 13.2 V DC (negative ground)
- Current drain (approx.):

Tx at 25 W	6.0 A (IC-F310) 7.0 A (IC-F410)
Rx max. audio standby	700 mA 200 mA
- Antenna connector : SO-239 (50 Ω)

- Dimensions : 140(W) × 40(H) × 170(D) mm
- Weight : 1.2 kg

TRANSMITTER

- Output power : 25 W (at 13.2 V DC)
- Modulation system : Variable reactance frequency modulation
- Max. freq. deviation : ±2.5 kHz (narrow)
±5.0 kHz (wide)
- Spurious emissions : 0.25 μV
- Adjacent ch. power : 60 dB (narrow)
70 dB (wide)
- Mic. connector : 8-pin modular (600 Ω)

Measurement made in accordance with ETS 300 088. All stated specifications are subject to change without notice or obligation.

RECEIVER

- Intermediate freq. : 1st 31.05 MHz (IC-F310)
46.35 MHz (IC-F410)
2nd 450 kHz
- Sensitivity : -4 dBμV (emf, IC-F310)
-2 dBμV (emf, IC-F410)
- Squelch sensitivity : -7 dBμV (emf, IC-F310)
-5 dBμV (emf, IC-F410)
- Adj. ch. selectivity : 60 dB (narrow)
70 dB (wide)
- Spurious response : 70 dB
- Intermodulation : 65 dB
- Audio output power : 3 W typical at 5% distortion with a 4 Ω load
- Ext. SP connector : 2-conductor 3.5 (d) mm (1/8")/4 Ω

Supplied Accessories

- Hand microphone
- DC power cable
- Mounting bracket kit
- Key assign stickers
- Fuses

OPTIONS

- **UT-96 5-TONE UNIT**
Provides the transceiver with 5-tone decoder capabilities
- **UT-105 SmarTrunk II™ Logic Board***
Provides SmarTrunk II™ capabilities.
*SmarTrunk II™ is a trademark of SmarTrunk Systems Inc.

- **SP-5 EXTERNAL SPEAKER**
Large speaker provides good audio quality.
Input impedance: 4 Ω; Max. input power: 5 W
- **SP-10 EXTERNAL SPEAKER**
Compact and easy-to-install.
Input impedance: 4 Ω; Max. input power: 5 W

UT-96



SP-5



SP-10



Icom Inc. 6-9-16, Kamihigashi, Hirano-ku, Osaka 547, Japan Phone: 06 793 5302 Fax: 06 793 0013

Count on us!

Icom America Inc.

Corporate Headquarters
2380 119th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
Telex: 152210 ICOM AMER BVUE

Customer Service
Phone: (425) 454-7519

Icom Canada

A Division of Icom America Inc.
3071 #5 Road, Unit 9, Richmond, B.C., V6X 2T4, Canada
Phone: (604) 273-7400 Fax: (604) 273-1900

Icom (Australia) Pty. Ltd.

A.C.N. 006 060 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0002

Icom (Europe) GmbH

Communication Equipment
Himmelgelster Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 332629

Icom Telecomunicaciones s.l.

"Edificio Can Castanyer" C/ta. Gracia a Menresa km. 14,750
08190 Sant Cugat Del Valles Barcelona, SPAIN
Phone: (3) 589 46 82 Fax: (3) 589 04 46

Icom (UK) Ltd.

Unit 9, Sea St., Haine Bay, Kent, CT9 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
Telex: 317210 BUREAU G

Icom France S.a

Zac de la Plaine, Rue Brindejonc des Moutains
BP 5804, 31505 Toulouse Cedex, France
Phone: 561 36 03 03 Fax: 561 36 03 00
Telex: 521515 ICOM FRA

Your local distributor/dealer:

Point electronics

A- 1060 Wien, Stumpergasse 41- 43

Tel.: +43/ 1/ 597 08 80/ 0 FAX: DW 40

www.point.at mail@point.at