

 ICOM

VHF MARINE TRANSCEIVER  
**IC-M35**



"Automatic Volume Adjustment"

"Noise Canceling Mic"

"Loud: Instant Maximum Audio"

## CLEAR VOICE BOOST

(Clear Voice + Voice Boost)

In marine environments there are many sources of noise that can affect the quality of your communication, such as engine noise, roar of waves and more. The IC-M35 constantly transmits clear voice and provides boosted audio even in those circumstances and ensures your conversation is sent and received as clearly as possible no matter how noisy the background is!

## And yes, it floats too!

Continuing the legacy from the IC-M33, the IC-M35 floats for you to be able to retrieve it if you should ever lose it overboard. The IC-M35 floats even when the optional speaker microphone, HM-165 is attached.



**BUOYANT**

**Waterproof**

1m depth for 30 minutes



### LOUD button

When you need an instant "boost" in the volume, a simple push of the "LOUD" button gives you full volume immediately. In addition, holding the "LOUD" button mutes the audio output.

### Noise cancelling microphone

The sub-microphone on the rear panel inverts phase and cancels out ambient noise from the main microphone. As a result, the IC-M35 reduces the affect of background noise (particularly treble noise) from the transmitted signal and makes it easier to catch voice communication.

### Automatic volume adjustment

When in an engine room or high noise environment, the sub-microphone detects the ambient noise and the IC-M35 automatically increases the volume output to suit the surrounding environment.

### Low power consumption

Although the IC-M35 delivers a high 6W\*1 RF output and 700mW audio output, its current saving circuit offers a practical 8 hours\*2 of operating time with the supplied 980mAh Lithium-Ion battery pack.

\*1 Depending on version.

\*2 Typical operation with Tx (Hi): Rx: standby=5:5:90

### Large buttons and slim dimensions

Thanks to the large, easy-to-operate buttons, the IC-M35 provides intuitive operation. A pinched-waist slender body makes it easy to hold and carry the radio, and is surprisingly compact for a floating radio.

### Other features

- Waterproof construction equivalent to IPX7 (1m depth for 30 minutes)
- Dual/Tri-watch functions
- 4-step battery life indicator
- Auto scan function
- Instant access to Ch 16 or programmable call channel

## SPECIFICATIONS

### GENERAL

- Frequency range Tx : 156.000-161.450MHz  
Rx : 156.000-163.425MHz
- Usable channels : INT, USA\* channels;  
70 programmable channels  
(\* Depending on version)
- Current drain (at 7.4V DC) :  
Tx 6W output 1.5A typical  
5W output 1.3A typical  
Rx AF max.  
Internal speaker 300mA typical  
External speaker 200mA typical  
Power save 10mA typical
- Operating temperature range : -15°C to +55°C
- Antenna impedance : 50Ω (STUD)
- Dimensions (W×H×D) : 62×139.5×43 mm  
(projections not included)
- Weight (approx.) : 295g (with BP-252, MB-109 and antenna)

### TRANSMITTER

- Output power (Hi/Low) : 6/1W\*  
2/1W (with alkaline battery)  
\* Australia version 5/1W  
\* German version 1/0.5W
- Max. frequency deviation : ± 5.0kHz
- Frequency error : ± 1.5kHz
- Spurious emissions : 0.25µW
- Adjacent channel power : 70dB
- Audio harmonic distortion : Less than 10% (at 60% dev.)
- Residual modulation : 40dB

### RECEIVER

- Sensitivity (20dB SINAD) : -2dBµ emf typical
- Squelch sensitivity : -6dBµ emf typical (threshold)
- Adjacent Ch. selectivity : 70dB
- Spurious response : 70dB\*  
\* Australia version 65dB
- Intermodulation rejection : 68dB
- Hum and noise ratio : 40dB
- Audio output power (at 10% distortion) :  
Internal speaker 700mW typical (with a 16Ω load)  
External speaker 200mW (with an 8Ω load)

**Supplied accessories**

- Battery pack, BP-252
- Belt clip, MB-109
- Antenna, FA-SC58V
- Battery case, BP-251 (UK version only)
- Battery charger, BC-173
- AC adapter, BC-174E or BC-147SV\*
- Hand strap

(\* Not supplied depending on version.)

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

## OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



**BP-251 BATTERY CASE**  
Battery case for AAA (LR03)×5 alkaline cells. Output power: 2W.  
**BP-252 Li-Ion BATTERY PACK 7.4V, 950mAh (min.) 980mAh (typ.).** Provides 8 hours operating time (approx.).  
(Typical operation with Tx (Hi): Rx: standby=5:5:90)



**BC-173 DESKTOP CHARGER**  
+ **BC-147SE/SV AC ADAPTER**  
Charges the battery pack, BP-252, in 10 hours (approx.).



**BC-162 DESKTOP CHARGER**  
+ **BC-145SE AC ADAPTER**  
Rapidly charges the battery pack, BP-252, in 2 hours (approx.).



**HM-165 SPEAKER-MICROPHONE**  
Waterproof construction equivalent to IPX7 (1 m depth for 30 min.).



**MB-109 BELT CLIP**  
Alligator type. Same as supplied.



**FA-SC58V ANTENNA**  
Soft flexible antenna. Same as supplied.

Please note : The noise cancellation can produce little or no effect in some conditions depending on type of noise, or the position and distance between the noise source and the microphone, etc. The noise cancellation does not work when an optional external speaker-microphone is connected.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. All other trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

**Count on us!**

**Icom America Inc.**  
2380 116th Avenue NE,  
Bellevue, WA 98004, U.S.A.  
Phone : +1 (425) 454-8155  
Fax : +1 (425) 454-1509  
E-mail : [sales@icomamerica.com](mailto:sales@icomamerica.com)  
URL : <http://www.icomamerica.com>

**Icom New Zealand**  
146A Harris Road, East Tamaki,  
Auckland, New Zealand  
Phone : +64 (09) 274 4062  
Fax : +64 (09) 274 4708  
E-mail : [inquiries@icom.co.nz](mailto:inquiries@icom.co.nz)  
URL : <http://www.icom.co.nz>

**Icom (UK) Ltd.**  
Unit 9, Sea St., Herne Bay,  
Kent, CT6 8LD, U.K.  
Phone : +44 (0)1227 741741  
Fax : +44 (0)1227 741742  
E-mail : [info@icomuk.co.uk](mailto:info@icomuk.co.uk)  
URL : <http://www.icomuk.co.uk>

**Asia Icom Inc.**  
6F No. 68, Sec. 1 Cheng-Teh Road,  
Taipei, Taiwan, R.O.C.  
Phone : +886 (02) 2559 1899  
Fax : +886 (02) 2559 1874  
E-mail : [sales@asia-icom.com](mailto:sales@asia-icom.com)  
URL : <http://www.asia-icom.com>

**Icom Canada**  
Glenwood Centre #150-6165 Highway 17,  
Delta, B.C., V4K 5B8, Canada  
Phone : +1 (604) 952-4266  
Fax : +1 (604) 952-0090  
E-mail : [info@icomcanada.com](mailto:info@icomcanada.com)  
URL : <http://www.icomcanada.com>

**Icom (Europe) GmbH**  
Communication Equipment  
Himmelgeister Str. 100,  
D-40225 Düsseldorf, Germany  
Phone : +49 (0)211 346047  
Fax : +49 (0)211 333639  
E-mail : [info@icomeurope.com](mailto:info@icomeurope.com)  
URL : <http://www.icomeurope.com>

**Icom France s.a.s.**  
Zac de la Plaine,  
1 Rue Brindejonn des Moulinais, BP 45804,  
31505 Toulouse Cedex 5, France  
Phone : +33 (5) 61 36 03 03  
Fax : +33 (5) 61 36 03 00  
E-mail : [icom@icom-france.com](mailto:icom@icom-france.com)  
URL : <http://www.icom-france.com>

**Icom (Australia) Pty. Ltd.**  
Unit 1 / 103 Garden Road,  
Clayton, VIC 3168 Australia  
Phone : +61 (03) 9549 7500  
Fax : +61 (03) 9549 7505  
E-mail : [sales@icom.net.au](mailto:sales@icom.net.au)  
URL : <http://www.icom.net.au>

**Icom Spain S.L.**  
Ctra. Rubi, No. 88 "Edificio Can Castanyer"  
Bajos A 08174, Sant Cugat del Valles,  
Barcelona, Spain  
Phone : +34 (93) 590 26 70  
Fax : +34 (93) 589 04 46  
E-mail : [icom@icomspain.com](mailto:icom@icomspain.com)  
URL : <http://www.icomspain.com>

**Icom Polska**  
81-850 Sopot, ul. 3 Maja 54, Poland  
Phone : +48 (58) 550 7135  
Fax : +48 (58) 551 0484  
E-mail : [icompolkska@icompolkska.com.pl](mailto:icompolkska@icompolkska.com.pl)  
URL : <http://www.icompolkska.com.pl>

Your local distributor/dealer:

**Point electronics**

A- 1060 Wien, Stumpergasse 41 - 43

Tel.: +43/ 1/ 597 08 80/ 0

FAX: +43/ 1/ 597 08 80/ 40

[www.point.at](http://www.point.at) [www.icom.at](http://www.icom.at)  
[mail@point.at](mailto:mail@point.at)